

With fast cutting performance, good service life and low heat generation, these wheels are recommended for general purpose cut-off use on stainless steel.

Abrasive: Aluminum oxide A

Workpiece materials

Stainless steel (INOX)
Also suitable for carbon steel and all ferrous metals.



**CONTAMINATION FREE
RATED FOR STAINLESS STEEL (INOX)**

Applications

Cutting of sheet metal, sections and solid materials

Recommendations for use

■ .040", .045" thickness for fast, convenient cutting with minimized burr formation.

■ .040" cut-off wheels are highly recommended for cordless angle grinders due to their narrow kerf, their superior cutting characteristics and optimal handling. They deliver more cuts per battery charge, making them very economical.

PFERDERGONOMICS®




PFERDEFFICIENCY®



PFERD specification number

A 46/60 P PSF-INOX



Diameter x thickness nominal [Inches]	Thickness metric [mm]	Bore [Inches]	EDP number		Max. RPM
Flat (type 1)					
4-1/2 x .040	1.0	7/8	63540	25	13,300
4-1/2 x .045	1.6	7/8	63550	25	13,300
5 x .040	1.0	7/8	63541	25	12,200
5 x .045	1.6	7/8	63551	25	12,200
6 x .045	1.6	7/8	63552	25	10,200

