

Produced with 40% more zirconia coated material than standard PSF flap discs, PSF ZIRKON-EXTRA flap discs provide a long service life, an improved surface finish and a soft, cushioned grinding effect.

Abrasive: Zirconia alumina Z

Workpiece materials

Steel, stainless steel (INOX)



**CONTAMINATION FREE
RATED FOR STAINLESS STEEL (INOX)**

Applications

Surface grinding, weld grinding, blending, chamfering, deburring

Recommendation for use

While these discs perform on all power outputs, high-powered angle grinders (please refer to the table on page 4: 4-1/2" electric angle grinder = 8+ amps) will achieve optimal results.

PFERDERGONOMICS®



PFERDEFFICIENCY®



PFERD specification number

PSF Z-EXTRA

**Steel/stainless steel (INOX)
PSF ZIRKON-EXTRA**



Diameter [Inches]	Unthreaded arbor hole					Threaded arbor hole					Max. RPM			
	Bore [Inches]	Grit and EDP number					Thread	Grit and EDP number						
		36	40	60	80	120		36	40	60			80	120

Flat (PFF – type 27)



4-1/2	7/8	60457	60458	60460	60461	60462	5/8-11	60485	60486	60488	60489	60490	13,300	10
5	7/8	60464	60465	60467	60468	60469	5/8-11	60492	60493	60495	60496	60497	12,200	10
6	7/8	60471	60472	60474	60475	60476	5/8-11	60499	60500	60502	60503	60504	10,200	10
7	7/8	60478	60479	60481	60482	60483	5/8-11	60506	60507	60509	60510	60511	8,500	10

Conical (PFC – type 29)



4-1/2	7/8	60625	60626	60628	60629	60630	5/8-11	60653	60654	60656	60657	60658	13,300	10
5	7/8	60632	60633	60635	60636	60637	5/8-11	60660	60661	60663	60664	60665	12,200	10
6	7/8	60639	60640	60642	60643	60644	5/8-11	60667	60668	60670	60671	60672	10,200	10
7	7/8	60646	60647	60649	60650	60651	5/8-11	60674	60675	60677	60678	60679	8,500	10

The POLIFAN® PSF ZIRKON-TRIM has a composite backer which can be trimmed to extend the service life. The 5/8-11 quick-change version is produced with a zinc hub.

Abrasive: Zirconia alumina Z

Workpiece materials

Steel, stainless steel (INOX)



**CONTAMINATION FREE
RATED FOR STAINLESS STEEL (INOX)**

Application

Surface grinding, weld grinding

Recommendation for use

While these discs perform on all power outputs, high-powered angle grinders (please refer to the table on page 4: 4-1/2" electric angle grinder = 8+ amps) will achieve optimal results.

PFERDERGONOMICS®



PFERDEFFICIENCY®



PFERD specification number

PSF Z-TRIM

**Steel/stainless steel (INOX)
PSF ZIRKON-TRIM**

NEW



Diameter [Inches]	Unthreaded arbor hole			Threaded arbor hole			Max. RPM			
	Bore [Inches]	Grit and EDP number			Thread	Grit and EDP number				
		40	60	80		40			60	80

Flat (PFF – type 27)



4-1/2	7/8	68098	68099	68100	5/8-11	68158	68159	68160	13,300	10
5	7/8	68104	68105	68106	5/8-11	68164	68165	68166	12,200	10
7	7/8	68116	68117	68118	5/8-11	68176	68177	68178	8,500	10